

9G & 9M Series

CUT VINYL

Data sheet

Description

High performance calendered film in luxurious high glossy colors and matte colors, user-friendly with excellent dimensional stability and weeding characteristic.

| | |
|------------------|-----------------------------------------|
| Face film | Monomeric PVC made in Taiwan |
| Thickness | 80 µm (3.2mil) ±5% |
| Color and Finish | 55 high glossy colors & 55 matte colors |

Release liner

Premium quality Single-PE coated silicone paper, 135 gsm ±5% imported from Japan.

| | |
|--------|-----------------------|
| Finish | With GraphicTAC brand |
|--------|-----------------------|

Adhesive

Clear, permanent, solvent-based adhesive, non-residue, made in Taiwan.

| | |
|--------------------|----------------------------|
| Type | Acrylic |
| Apply Temp. | +10°C ~ +40°C |
| Adhesion (20 min) | 1,200 g/25mm |
| Adhesion (24 hour) | 1,500 g/25mm |
| Cohesion | 24 hours with 1 kg loading |

Application

Designed for use on cutting plotter system, for decoration, indoor and outdoor general signage, automotive and window graphics. Suitable for curved application.

Storage

Shelf life is 1 years in original packaging, at 25°C and 50% relative humidity.

Length and Width

| | |
|--------|---------------------------|
| Length | 50 meters |
| Width | 0.61m (24") / 1.22m (48") |

Durability and Exposure & Climate Condition

Outdoor durability: Up to 3 years depending on exposure angle and climate condition, based on unprinted film vertical exposure.